

KVAR	VAC rms	Frequency (Hz)	Cap (uF)	Current rms	Case	Sections	Width (in)	Length (in)	Height (in)	Weight (kg)
965	1250	100	985	772	dead	1	8.00	22.00	28.00	94
1500	2400	200	207	625	dead	6	6.25	13.50	28.00	65
1750	800	250	1740	2188	dead	1	8.00	22.00	28.00	94
2900	1250	300	985	2321	dead	1	8.00	22.00	28.00	94
1270	1500	300	300	850	dead	1	6.25	13.50	26.00	42
4000	1800	300	650	2210	dead	1	8.00	22.00	31.00	104
4300	2400	300	396	1792	dead	1	8.00	22.00	32.00	107
4000	2800	300	271	1428	dead	1	8.00	22.00	28.00	94
5133	3000	300	303	1711	dead	1	7.50	22.00	32.00	100
4800	2800	400	244	1715	dead	1	7.50	22.00	28.00	88
4200	1250	500	856	3360	live	2	8.00	22.00	28.00	94
4780	2500	500	244	1912	dead	1	7.50	22.00	28.00	88
1000	1250	600	169	800	dead	6	6.25	13.50	12.50	30
7200	3000	600	255	2500	dead	1	7.50	22.00	31.00	98
1900	800	1000	473	2375	dead	8	6.25	13.50	20.50	50
2600	1090	1000	348	2385	live	1	6.50	13.50	18.50	32
2600	1250	1000	265	2080	dead	8	6.25	13.50	21.50	52
3000	1250	1000	306	2400	dead	1	6.25	13.50	21.50	39
3300	1850	1000	153	1784	dead	1	6.25	13.50	18.50	30
13500	3000	1000	197	3722	dead	2	8.00	22.00	28.00	94
4800	1000	1200	637	4800	dead	2	8.00	22.00	28.00	94
1200	1250	1200	102	960	live	6	5.13	13.50	13.00	26
2000	1250	1200	170	1600	live	6	5.25	13.50	15.25	30
1200	1500	1200	71	800	live	6	5.38	13.50	13.00	27
3000	1500	1200	177	2000	live	8	6.25	13.50	17.50	42
4320	1800	1200	177	2400	dead	1	6.00	22.00	13.50	34
7350	3300	1500	72	2272	dead	1	6.50	13.50	29.00	49
900	400	3000	298	2250	dead	8	6.25	13.50	13.00	31
450	800	3000	37	565	live	6	4.13	13.50	7.00	12
900	800	3000	75	1125	live	4	4.13	13.50	13.00	21
1900	800	3000	158	2375	live	8	6.25	13.50	13.00	31
1200	1250	3000	41	960	live	8	4.13	13.50	9.00	14
3000	1250	3000	102	2400	live	8	6.13	13.50	14.00	33
2333	1500	3000	55	1710	live	8	4.13	13.50	13.00	21
3600	1800	3000	59	2000	live	8	5.13	13.50	13.00	26
3900	3000	6000	12	1300	dead	8	4.63	13.50	15.25	28
900	440	9600	77	2045	live	6	4.13	13.50	13.00	21
450	800	9600	12	562	live	6	4.13	13.50	7.00	12
1200	800	9600	31	1500	live	5	4.13	13.50	7.00	12
1900	800	10000	47	2378	live	8	4.38	13.50	9.50	16
3000	1250	10000	31	2400	live	8	5.25	13.50	13.00	26
3000	2500	10000	8	1200	live	6	5.75	13.50	13.50	30
1050	800	25000	10	1320	live	6	4.13	13.50	7.00	12
3000	2000	30000	4	1508	live	7	5.13	13.50	15.25	30
955	800	50000	4.8	1200	live	6	6.13	13.50	15.00	36
1235	1250	50000	2.5	988	live	6	6.13	13.50	14.25	34
3150	3000	50000	1.1	1050	dead	6	6.25	13.50	14.00	34
1000	1250	100000	1	800	live	6	4.50	13.50	6.00	11
1000	1250	200000	0.51	800	live	6	4.50	13.50	5.00	10
1000	2500	200000	0.13	404	live	6	4.50	13.50	5.00	10
1000	1250	450000	0.227	800	live	6	4.50	13.50	5.00	10
1000	2500	450000	0.06	404	live	6	4.50	13.50	5.00	10

Modifications for all ratings, case, and sections are available.  
Consult factory with detail requirements or request technical dialog.



e-mail: sales.caps@nwl.com, ph: 252-747-5943 x 225, fax: 252-747-8979